



Stepsolve Stainless Steel

INDIVIDUAL STUDS



PRODUCT DESCRIPTION

An individual tactile ground surface indicator manufactured from austenitic stainless steel designed to warn the vision impaired of an impending hazard or to provide directional guidance. As part of The Disability Discrimination Act (DDA) compliance, it is mandatory to provide Tactile Warning Indicators (TGSIs) to stairs, ramps and other changing conditions.

DIMENSIONS & FEATURES

- R13 anti-slip rated
- Major diameter of 35mm and a minor diameter of 25mm
- Protrusion height of 5mm
- Concentric ring with smooth side face
- Available with or without a fixing spigot diameter of 6mm x 15mm long
- Strong retention to all substrates - concrete, timber, bitumen and most other surfaces
- Manufactured from one piece in 316 stainless steel to ensure long lasting and maintenance free performance
- Resistant to heavy traffic abuse and maintenance machinery
- Attractive high polish and mill finish.

LUMINANCE CONTRAST & COMPLIANCE

In accordance with Australian Standards, a minimum luminance contrast of 45% must be provided between a monochromatic tactile indicator and the surrounding substrate.



The company with every floor and step safety solution.



Stepsolve Tactile Indicators allow specifiers to select the most appropriate luminance contrast for any given application and aesthetic requirement.

Our tactiles comply with: AS/NZS 1428:4.2002 Design for access and mobility. AS/NZS 4586:1999 Slip resistance classification for new pedestrian surface materials.