# Stepsolve Anti-Slip

SAFFTY TAPES



## **BENEFITS**

Stepsolve Anti-Slip tapes offer a low cost, immediate solution to slip problems in internal and external areas where there is a medium level of pedestrian activity.

Stepsolve Anti-Slip tapes are R13 rated and comply with the anti-slip Standards and Building Codes.

Manufactured from a unique combination of aluminium oxide which is diamond hard and a thick flexible plastic carrier to provide a hard, tough, durable and long lasting solution. They are marine grade and are manufactured from a water resistant carrier and adhesive.

The tapes feature a peel off, self-adhesive backing and are easily cut to size for fixing to metal, wood and concrete.

They are particularly suitable for use on clean, dry, flat areas but can be fixed to uneven surfaces if a primer is used.

Stepsolve Anti-Slip tapes range from 25mm to 300mm in width and are 18.3 metres in length.

#### **AVAILABLE IN 6 COLOURS**

Stepsolve Anti-Slip tapes are available in 6 colours to meet the luminance contrast requirements of AS/NZS1428.1 - Design for access and mobility.

- Black
- · Photo Luminescent
- Grey
- White
- Yellow
- · Clear
- Hazard Strip (Black & Yellow)

Photo-luminescent tape is ideal for stainwells, ramps & escape routes; and white and clear water resistant tape for showers, bathrooms and other wet areas. The clear tape is suitable for use in listed buildings where the use of coloured tape may not be appropriate.

# **SURFACE PREPARATION**

Apply tape only to a clean, dry, grease & dust free surface. Press firmly into position. Best adhesion at 23C.



## **TECHNICAL DATA**

MINERAL PARTICLES - Aluminium Oxide

GRADE - Coarse Grit 24 & 35 Medium 60

HOLDING MEDIUM - Solvent Acrylic Adhesive

APPLICATION TEMP - 5 up to 50C

ADHESION - 600gm/cm

THICKNESS - 0.8mm +/- 0.2mm

TENSILE STRENGTH – 7KgF / 25mm

ELONGATION AT BREAK - 80%

RESISTANCE TO WEAR – 12 months

RESISTANCE TO GREASE -

8 months

STAINING OF ADHESIVE – No Evidence of migration









The company with every floor and step safety solution.