

TacWay Tile 300 x 300mm - Peel & Stick Tactile pad

PRODUCT DESCRIPTION

TacWay Tile Tactile guidance products are an easy, effective and fuss free way of providing guidance cues that conform with the Disability Discrimination Act (DDA). The TacWay Tile is supplied with a super strong PSA peel and stick backing and can be installed internally and some external surfaces to provide a quick and cost effective means of conforming to the Australian standards and NCC requirements.

DIMENSIONS

Designed to conform to the Australian Standards and the National Construction Codes

Major diameter of 35mm, Minor diameter of 25mm

Stud height of 5mm, Base thickness of 2.5mm

TacWay Tile is manufactured in a standard tile size of 300x300mm with a square edge to ensure a tight join with minimal gaps.

PRODUCT RANGE

TacWay Tile is available in both hazard and directional formats in 5 standard colours, including Ivory, Yellow, Grey and Black. Other colours can be custom made on request.

FEATURES

1. R12 anti-slip rated in Accordance with the Australian Standards AS4586.
2. TacWay Tile is manufactured from strong, durable polyurethane polymer which has a greater wear resistance than steel. This provides a flexible, hard wearing and long lasting tactile that is suitable for extreme high traffic areas such as in the transport and education sectors.
3. Will not discolour, crack or degrade over time
4. Fast, easy installation. DIY, no special technical skills and no down-time – can be walked on immediately. Low cost and effective supply/install.

APPLICATION:

TacWay Tile is suitable for all internal surfaces and some external surfaces such as concrete and bitumen when prepared with a suitable moisture barrier.

WARRANTY

STEPSOLVE Australia provides a 10 year manufacturer's warranty.

COMPLIES WITH

1. AS/NZS 1428:4.2002 Design for access and mobility
2. AS/NZS 4586:1999 Slip resistance classification for new pedestrian surface materials

